1 WARNING: (1) (1) (2)











- All the pneumatic tools should only be used as hand operated tools. They are powered by compressed air and are not insulated against electric shock.
- Always turn off the air supply and disconnect the air hose before changing or replacing any inserted tool and accessory.
- Before using these tools, make sure that all couplings and plugs are securely fastened. Air hoses which are under pressure may lash out when disconnecting, that can lead to serious injury!
- High sound levels may cause hearing damage. Always wear hearing protection when operating this tool.
- Wearing eye/face protection can reduce the danger of high-speed materials being emitted from the tool. Make sure that the direction of the spark generated from the cutting wheel grinding wheel or shank stone is properly directed so as to not create a hazard..
- Always wear gloves to reduce risk
- User must wear proper clothing. Loose clothing, long hair, stings, straps, belts and jewelry should not be worn when operating this tool.
- Long periods of prolong use will cause fatigue. Periodic breaks are recommended for user safety.
- It is recommended to stop operating the tool whenever discomfort, tingling or pain occurs during use.
- Make sure there is no gas or combustible material stored near the tool when servicing, changing insert tools, or storage.
- Wearing proper breathing protection to avoid inhale dust or handling debris from working process, which can be harmful to the health.



A STRONG BRAND LISTENS TO ITS CUSTOMERS

When we develop products such as our new, extremely small and handy air impact wrench NC-4610, M7 customers are our main driving force and focus. By building trust and excellent communication channels with our partners, distributors and channel customers, we very quickly get to understand what it is that they are looking and what motivates their choice of air tools.

As a designer, manufacturer and distributor of tools, we are just as committed to bringing the most reliable, efficient, ergonomic tools to the market as we are to fulfilling our promise of excellent service and support to our clients.

M7'S SUCCESS IS A TEAM EFFORT!

Mighty Seven, or M7 as it is affectionately called by thousands of users world-wide, is much more than just a good manufacturer of air tools. In fact, M7 provides a total brand solution for its air tool partners and consumers. M7's team is composed of a strong network of International air tool experts and an enthusiastic team of engineers, designers, marketeers and administration personnel.



EXPERTISE AND KNOW-ROW

M7 clients are very demanding and nothing short of excellence in product quality and fully committed support will do for them. We may sometimes feel that it is a lot to ask of a relatively new brand, but we embrace the challenge with open arms. We have been manufacturing tools for decades and our expertise in that field helps us better understand our clients' needs.

In terms of quality, we ensure that all the M7-branded products that we sell reflect our commitment to providing tools that are extremely reliable and perform. In order to achieve our standards of quality, our tools are tested thoroughly in our factory, using equipment such as testing equipments used in M7 includes: computerized fatigue testing machines, digital torque testing machines, multi-functional testing machines, grinding efficiency testers, run-out testers, digital measuring projectors, environmental testing chamber, grinding and polishing machines, infrared tachometers, vibrations testers and decibel level detectors.



THIS IS ONLY THE DECIMALNE

Although we have been in the industry for more than 2 decades, M7 has only existed as a brand for Over ten years. Nevertheless, the inroads that we have made in many important markets, such as automotive, have led us to believe that our combination of great partner support and quality air tools is our key to succeeding.

M7 has made its bed and the focus is clearly on providing the right combination of marketing support, customer training and new product development as the way forward. When we print our slogan "greater partner support" we see it not so much as wishful thinking, but more as a M7 "truth", a code by which we live daily.







THE MITTER OF THE PROPERTY OF

As of today, Mighty-seven offers a wide Pneumatic product spectrum. And how does Mighty Seven know which tools you need? M7 listens to you.

CONTENT

- 08 _ AIR IMPACT WRENCH
- 20 AIR RATCHET WRENCH
- 22 AIR DIE GRINDER
- 25 _ AIR ANGLE GRINDER
- 30 _ AIR BELT SANDER
- 32 _ AIR SANDER
- 38 _ AIR SHEAR
- 39 _ AIR SAW
- 40 _ AIR DRILL
- 47 _ AIR SCREWDRIVER
- 54 AIR HAMMER
- 56 . AIR HYDRAULIC RIVETER
- 62 _ AIR GREASE GUN
- 64 _ AIR BLOW GUN
- 66 L AUTO REPAIR TOOL
- 70 _ FILTER, REGULATOR, LUBRICATOR
- 72 _ AIR HOSE & AIR ADAPTER
- 74 _ MOBILE CABINETS
- **76** IMPACT SOCKET & ACCESSORIES
- **80** AFTER MARKET SUPPORT
- 83 _ AFTER MARKET REPAIR KITS
- 84 _ TROUBLE SHOOTING

LEVEL

M7 has categorised its tools into three distinctive levels for user convenience. These level classifications are for reference only.



Efficiency / Performance

Easy to use to handle tasks quickly, these tool embody efficiency and performance.



Strength

Tools provide high torque force, superior grinding power and high cutting energy.



Endurance

Built to last, product longevity and low failure rate are characteristics associated with these tools.

APPLICATION

Application icons have been designed to provide visual references that suggest industry specific features or usability. These application icons are for reference only.









Boat



Motorcycle Automotive

utomotive Industry

Agriculture



AIR IMPACT WRENCH

SUPPORT | VALUE | EXPERTISE

MIGHTY SMALL MIGHTY POWERFUL MIGHTY SEVEN













NC-4610Q

1/2"Drive Super Mini Impact Wrench

Jumbo Hammer Type

MIGHTY QUIET

- Best in class performance for a tool of just 4-9/16" (115.5 mm)L x 7-1/8"(180mm)H, the weight will be 3.52 lbs (1.6 Kgs).
- The minimum size of this tool will allow greater access to tight and limited spaces.
- Small but with greater power. Reach 500-ft-lb in just 5 seconds.
- Easy to remove vehicle's crankshaft pulley without removing anything else.
- O Low noise sound level 85 db.
- Common application to Narrow working place and Agricultural maintenance.











NC-3111

3/8" Drive Air Impact Wrench









10 pieces are packed in one carton



NC-3210

3/8" Drive Air Impact Wrench

Twin Hammer Type









10 pieces are packed in one carton



NC-3410

3/8" Drive Air Impact Wrench

Rocking Dog Type









20 pieces are packed in one carton



NC-4131/4141

1/2" Drive Air Impact Wrench

Pin Clutch Type





10 pieces are packed in one carton

AIR IMPACT WRENCH

SUPPORT | VALUE | EXPERTISE



10 pieces are packed in one carton



10 pieces are packed in one carton



NC-4213/4223 1/2" Drive Air Impact Wrench

Twin Hammer Type





10 pieces are packed in one carton



NC-4217 1/2" Drive Air Impact Wrench

Twin Hammer Type





8 pieces are packed in one carton

	Square Drive	Bolt Capacity	Torque Range FT-LB (Nm)		lax rque	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Nei Wei		Air Hose	Sound Pressure	Vibration Level
						№	□ Þ ₹		l ← L →I	(lb)	kg	□	?)))	(((O)))
NC-3111	3/8"	1/2"(13)	70-130(95-176)	175	237	9000	4.0(113)	90 (6.3)	6-7/16" (163)	3.5	1.6	3/8"	93.3	4.1
NC-3210	3/8"	1/2"(13)	100-300(136-407)	430	583	10000	4.0(113)	90 (6.3)	5-5/8" (142)	3.3	1.5	3/8"	92.1	3.6
NC-3410	3/8"	3/8"(10)	5-50(7-68)	88	119	10000	2.5(71)	90 (6.3)	6-1/4" (159)	1.75	0.8	3/8"	92.1	3.6
NC-4131	1/2"	5/8"(16)	150-350(203-475)	550	746	7000	4.2(119)	90 (6.3)	7-7/8" (200)	5.3	2.4	3/8"	95.1	2.7
NC-4141	1/2"	5/8"(16)	150-350(203-475)	550	746	7000	4.2(119)	90 (6.3)	9-3/8" (238)	5.5	2.5	3/8"	95.1	2.7
NC-4210	1/2"	5/8"(16)	150-350(203-475)	530	719	10000	4.2(119)	90 (6.3)	5-5/8"(142)	3.5	1.6	3/8"	90.6	2.8
NC-4210N	1/2"	5/8"(16)	150-350(203-475)	530	719	10000	4.2(119)	90(6.3)	5-5/8"(142)	3.5	1.6	3/8"	90.6	2.8
NC-4213	1/2"	5/8"(16)	180-400(244-542)	650	881	6500	4.2(119)	90(6.3)	7-3/16"(182)	6.2	2.8	3/8"	91.0	3.8
NC-4223	1/2"	5/8"(16)	180-400(244-542)	650	881	6500	4.2(119)	90(6.3)	9-1/4"(232)	6.4	2.9	3/8"	91.0	3.8
NC-4217	1/2"	5/8"(16)	150-320(203-434)	600	814	7000	4.2(119)	90(6.3)	7-1/4"(184)	5.6	2.5	3/8"	92.1	3.7





NC-4218

Twin Hammer Type

2" Drive Air Impact Wrench









8 pieces are packed in one carton



NC-4212/4222

2" Drive Air Impact Wrench











8 pieces are packed in one carton











NC-4216/4226

1/2" Drive Air Impact Wrench

Twin Hammer Type

- o Equipped with Twin Hammer Impact mechanism.
- Light weight composite main housing.
- O Forward / reverse and speed can be controlled simultaneously only with Multi-function switch.
- NC-4226 is equipped with 2" extended anvil.
- Integrated cylinder & rear end plate allows stable powerful output and easy to the maintenance dramatically.

10 pieces are packed in one carton



LIGHT 45% Compare with ordinary models

AIR IMPACT WRENCH

SUPPORT | VALUE | EXPERTISE



NC-4215/4225

1/2" Drive Air Impact Wrench

New Twin Hammer Type













8 pieces are packed in one carton



NC-4230Q/4240

1/2" Drive Air Impact Wrench

Twin Hammer Type















8 pieces are packed in one carton







NC-4258

1/2" Drive Air Impact Wrench

Twin Hammer Type

- o Equipped with Twin Hammer Impact mechanism.
- Quicker loosening saves time.
- Common applications are overall automotive service and body shop.

8 pieces are packed in one carton



	Square Drive	Bolt Capacity	Torque Range	Tor	lax que	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length		ight	Air Hose	Sound Pressure	Vibration Level
	Inch	Inch (mm)	FT-LB (Nm)	FT-LB	Nm	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	LBS	kg	Inch	dBA	m/s²
						No	□ •÷		l ∢ L → l	(lb)	kg	□ <u>▼</u>	((({ }	(((O)))
NC-4218	1/2"	5/8"(16)	150-350(203-475)	600	814	7000	4.2(119)	90(6.3)	7-1/2(190)	5.7	2.6	3/8"	97.5	4.4
NC-4212	1/2"	5/8"(16)	150-300(203-407)	650	881	7000	4.0(113)	90(6.3)	7-13/64"(182)	6.2	2.8	3/8"	86.1	3.7
NC-4222	1/2"	5/8"(16)	150-300(203-407)	650	881	7000	4.0(113)	90(6.3)	9-13/64"(233)	6.6	3.0	3/8"	86.1	3.7
NC-4215	1/2"	3/4"(19)	180-400(244-542)	700	949	6500	4.4(124)	90(6.3)	7-11/16"(195)	6.3	2.9	3/8"	91.4	3.8
NC-4225	1/2"	3/4"(19)	180-400(244-542)	700	949	6500	4.4(124)	90(6.3)	9-11/16"(246)	6.8	3.1	3/8"	91.4	3.8
NC-4230Q	1/2"	3/4"(19)	180-500(244-678)	700	949	6500	4.5(127)	90(6.3)	6-15/32"(164)	5.5	2.5	3/8"	85.0	4.5
NC-4240	1/2"	3/4"(19)	180-500(244-678)	700	949	7500	4.5(127)	90(6.3)	8-15/32"(215)	5.72	2.6	3/8"	87.0	4.5
NC-4216	1/2"	5/8"(16)	180-400(244-542)	700	949	9000	4.2(119)	90(6.3)	7-3/4"(195)	4.4	2.0	3/8"	93.9	4.5
NC-4226	1/2"	5/8"(16)	180-400(244-542)	700	949	9000	4.2(119)	90(6.3)	8-7/8"(225)	4.8	2.2	3/8"	93.9	4.5
NC-4258	1/2"	5/8"(16)	150-300(203-407)	580	786	7000	4.2(119)	90(6.3)	7-1/4"(185)	5.6	2.5	3/8"	93.2	4.4





NC-4610N

1/2" Drive Air Impact Wrench



Stubby impact sockets,6 points:5pcs 13, 17,19, 22, 24, mm









10 pieces are packed in one carton



NC-6113/6123

3/4" Drive Air Impact Wrench

Pin Clutch Type









4 pieces are packed in one carton











NC-6210Q/6220

3/4" Drive Air Impact Wrench

Twin Hammer Type

MIGHTY QUIET

- O Twin Hammer impact mechanism increases durability and efficiency.
- Stronger power output improves performance and accuracy.
 NC-6220 is equipped with 6" extended anvil.

8 pieces are packed in one carton



AIR IMPACT WRENCH

SUPPORT | VALUE | EXPERTISE



8 pieces are packed in one carton



4 pieces are packed in one carton



4 pieces are packed in one carton

	Square Drive	Bolt Capacity	Torque Range FT-LB (Nm)		Max rque Nm	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Ne Weig		Air Hose	Sound Pressure	Vibration Level
						№	□ ⊧≑		l ← L	(Ib)	kg	<u></u> □ <u>↓</u>	?)))	(((O)))
NC-4610N	1/2"	5/8"(16)	200-350(271-475)	500	678	9000	4.4(124)	90(6.3)	4-9/16"(115.5)	3.52	1.6	3/8"	93.0	2.8
NC-6113	3/4"	1"(25)	150-600(203-814)	850	1153	4500	7.0(198)	90(6.3)	10"(252)	10.1	4.6	1/2"	94.3	7.2
NC-6123	3/4"	1"(25)	150-600(203-814)	850	1153	4500	7.0(198)	90(6.3)	14-3/16" (360)	11.6	5.3	1/2"	94.3	7.2
NC-6212	3/4"	3/4"(19)	180-400(244-542)	950	1288	6300	4.4(124)	90(6.3)	7-61/64" (227)	6.6	3.0	1/2"	88.1	7.8
NC-6222	3/4"	3/4"(19)	180-400(244-542)	950	1288	6300	4.4(124)	90(6.3)	10-1/4" (260)	7.5	3.4	1/2"	88.1	7.8
NC-6210Q	3/4"	3/4"(19)	180-600(244-810)	1200	1627	6500	4.5(127)	90(6.3)	6-45/64" (170)	5.61	2.55	3/8"	85.0	4.5
NC-6215	3/4"	1"(25)	180-600(244-810)	950	1288	6500	7.0(198)	90(6.3)	9-7/32" (234)	10.0	4.5	1/2"	91.5	10.8
NC-6225	3/4"	1"(25)	180-600(244-810)	950	1288	6500	7.0(198)	90(6.3)	13-3/4" (350)	10.8	4.9	1/2"	91.5	10.8
NC-6216	3/4"	1-1/16"(27)	200-1000(271-1356)	1200	1627	6000	6.0(170)	90(6.3)	9-1/4" (235)	9.0	4.1	1/2"	91.2	5.0
NC-6226	3/4"	1-1/16"(27)	200-1000(271-1356)	1200	1627	6000	6.0(170)	90(6.3)	13-3/4" (350)	9.9	4.5	1/2"	91.2	5.0





NC-8212

1" Drive Air Impact Wrench

New Twin Hammer Type











4 pieces are packed in one carton



NC-8219

II Drive Air Impact Wrench

New Twin Hammer Type



2 pieces are packed in one carton









1" Drive Air Impact Wrench

Twin Hammer Type

- Twin Hammer Type and durable impact NC-8216/8226 mechanism structure with long life cycle.
 - O Weight: 8.4KG (Light weight type) 2 pieces are packed in one carton



PNEUMATIC TOOLS

SUPPORT | VALUE | EXPERTISE









NC-8321/8341

Air Impact Wrench

Pin Less Type



2 pieces are packed in one carton









NC-8311/8351

1 II Drive **Air Impact Wrench**

Pin Less Type



2 pieces are packed in one carton















Air Impact Wrench

New Twin Hammer Type











NC-8322/8342

1" Drive Air Impact Wrench

Pin Less Type



2 pieces are packed in one carton



	Square Drive	Bolt Capacity	Torque Range FT-LB (Nm)	M Tord	ax que Nm	Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure PSI (bar)	Overall Length	Nei Wei		Air Hose	Sound Pressure	Vibration Level
			•			No			l ∢ L →l	(lb)	kg	<u>↓</u>	?)))	(((O)))
		_	_	-	_	_		_			_	_	_	
NC-8212	1"	1-1/16"(27)	200-1000(271-1356)	1300	1762	6000	6.0(170)	90(6.3)	9-1/4"(235)	9.68	4.4	1/2"	91.2	5.0
NC-8216	1"	1-3/8"(33)	200-1600(271-2170)	1800	2441	6000	9.0(254)	90(6.3)	19-3/16"(487)	18.48	8.4	1/2"	102.0	9.3
NC-8226	1"	1-3/8"(33)	200-1600(271-2170)	1800	2441	6000	9.0(254)	90(6.3)	13-1/2"(343)	15.58	7.0	1/2"	102.0	9.3
NC-8219	1"	1-7/16"(36)	200-1600(271-2170)	1800	2441	4000	11.0(311)	90(6.3)	12-13/32"(315)	21.69	9.84	1/2"	103.4	16.7
NC-8321	1"	1-3/8" (33)	200-1600(271-2170)	1900	2576	4000	11.5(325)	90(6.3)	15" (380)	24.0	10.9	1/2"	97.0	6.3
NC-8341	1"	1-3/8" (33)	200-1600(271-2170)	1900	2576	4000	11.5(325)	90(6.3)	20" (510)	27.6	12.5	1/2"	97.0	6.3
NC-8311	1"	1-3/8" (33)	200-1600(271-2170)	2000	2712	4000	11.5(325)	90(6.3)	15" (380)	24.0	10.9	1/2"	101.0	7.3
NC-8351	1"	1-3/8" (33)	200-1600(271-2170)	2000	2712	4000	11.5(325)	90(6.3)	20" (510)	27.6	12.5	1/2"	101.0	7.3
NC-8232	1" 1	-7/16"(36)	200-1600(271-2170)	2100	2848	4000	11.0(311)	90(6.3)	20-13/32"(518)	24.86	11.3	1/2"	102	11.5
NC-8322	1" 1	-7/16"(36)	200-2000(271-2710)	2500	3390	3300	11.0(311)	90(6.3)	17-5/16"(440)	34.2	15.5	1/2"	93.9	8.8
NC-8342	1" 1	-7/16"(36)	200-2000(271-2710)	2500	3390	3700	11.0(311)	90(6.3)	20" (510)	38.0	17.3	1/2"	93.9	8.8



NC-8372

1" Drive Air Impact Wrench

Pin Less



1 piece are packed in one carton

NC-9223 1-1/2" Drive Air Impact Wrench

New Twin Hammer Type



1 piece are packed in one carton

NC-0410 [SET]

1/2" Drive Air Impact Wrench 10pcs



- 1pc Air Impact Wrench
- o 5pc Impact sockets, 6 points, standard length
 - 11, 13 mm, deep version 17, 19, 21mm
- 1pc Extension bar 5"
- 1pc Mini Oiler 1/4" female x 1/4" male
- 1pc 1/4" plug
- O 1pc Oil box

4 pieces are packed in one carton

Item No. Air Impact Wrench NC-0410M0 NC-4212 NC-0410M1 NC-4215



NC-0415 [SET]

PNEUMATIC TOOLS

SUPPORT | VALUE | EXPERTISE

1/2" Drive Air Impact Wrench 15pcs



- 1pc-1/2" Air Impact Wrench
- o 10pcs-Impact sockets, 6 points, standard length 9, 10, 11, 13, 14, 17, 19, 22, 24, 27mm
- 1pc-Extension bar 5"
- 1pc-Allen Key: 4mm
- 1pc-Mini Oiler 1/4" female x 1/4" male
- 1pc-1/4" plug

5 pieces are packed in one carton

Item No.

NC-0425M1

NC-0425M0



Air Impact Wrench

NC-0425M2

NC-0415M4



NC-0415M8

NC-0415M6

Air Impact Wrench NC-4131 NC-4217

NC-0615

Air Impact Wrench 15pcs



- 1pc-3/4" Air Impact Wrench
- o 8pcs-Impact sockets, 6 points, standard length 26, 27, 29, 30, 32, 35, 36, 38mm
- 1pc-Extension bar 7"
- 1pc-Universal Joint
- o 2pcs-Allen Key: 4mm, 5mm
- o 1pc-Mini Oiler 1/4"-6113,6215, 3/8"-6216
- o 1pc-1/4" plug 6113.6215, 3/8" plug 6216
- 1pc-O-Ring&Pin

2 pieces are packed in one carton

Item No.

NC-0615M0



NC-6113

Item No.

NC-0615M1



Item No.

Air Impact Wrench NC-6215

NC-0615M2

	Square Drive	Bolt Capacity	Torque Range	Max Torque	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Net Weight	Air Hose	Sound Pressure	Vibration Level
	Inch	Inch (mm)	FT-LB (Nm)	FT-LB Nm	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	LBS kg	Inch	dBA	m/s²
					No	₽		l - L - I	lb kg	□ <u>▼</u>	?)))	(((O))
NC-8372 NC-9223		1-7/16"(36)	200-2000(271-2710)			11.0(284)	90(6.3)	24-7/32" (615 17-3/4" (450)		1/2"	93.9	8.8



AIR RATCHET WRENCH

SUPPORT | VALUE | EXPERTISE



NE-251/351

1/4"Drive & 3/8" Drive Stubby Air Ratchet Wrench





20 pieces are packed in one carton



NE-211/311

1/4"Drive & 3/8" Drive Air Ratchet Wrench





20 pieces are packed in one carton



NE-321/421

3/8"Drive & 1/2" Drive Air Ratchet Wrench





20 pieces are packed in one carton



NE-332/432

3/8"Drive & 1/2" Drive Air Ratchet Wrench





20 pieces are packed in one carton









NE-462

1/2" Drive Air Ratchet Wrench



- O Pin-Clutch design mechanism generates 100N-M torque output
- Fasten to Stop design provides comfortable feel

10 pieces are packed in one carton

	Square Drive	Torque Range	То	Max rque	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length		et ight	Air Hose	Sound Pressure	Vibration Level
	<i>€</i>	FT-LB (Nm)	FT-LB		R.P.W	CFM (L/min)	PSI (bar)	Inch (mm)	LBS	kg	<u>↓</u>	() ()	(((O)))
					No		2 10	1+1	a	(kg)	<u></u>	8 11)	(((0)))
NE- 251	1/4"	5-15(6.7-20)	22	30	350	3.0(84.96)	90(6.3)	5"(125)	1.1	0.5	3/8"	89.0	4.4
NE- 351	3/8"	5-15(6.7-20)	22	30	350	3.0(84.96)	90(6.3)	5"(125)	1.1	0.5	3/8"	89.0	4.4
NE- 211	1/4"	5-15(6.7-20)	18	24	240	3.0(84.96)	90(6.3)	8"(205)	1.3	0.59	3/8"	89.6	3.9
NE- 311	3/8"	5-15(6.7-20)	18	24	240	3.0(84.96)	90(6.3)	8"(205)	1.3	0.59	3/8"	88.8	4.6
NE- 321	3/8"	10-35(13.5-47)	50	68	160	4.0(113.28)	90(6.3)	10-3/8"(265)	2.3	1.04	3/8"	91.0	3.9
NE- 421	1/2"	10-35(13.5-47)	50	68	160	4.0(113.28)	90(6.3)	10-3/8"(265)	2.3	1.04	3/8"	92.8	4.6
NE- 332	3/8"	10-45(13.5-61)	60	81	160	4.0(113.28)	90(6.3)	10-3/8"(265)	2.68	1.22	3/8"	90.5	4.4
NE- 432	1/2"	10-45(13.5-61)	60	81	160	4.0(113.28)	90(6.3)	10-3/8"(265)	2.68	1.22	3/8"	89.8	5.2
NE- 462	1/2"	10-55(13.5-74)	74	100	200	4.0(113.28)	90(6.3)	13"(330)	4.1	1.88	3/8"	84.0	2.5











20 pieces are packed in one carton



QA-311A(Metric Size) QA-311B(Inch Size) Air Die Grinder









12 pieces are packed in one carton













QA-315A(Metric Size) QA-315B(Inch Size) Air Die Grinder









12 pieces are packed in one carton

AIR DIE GRINDER

SUPPORT | VALUE | EXPERTISE







20 pieces are packed in one carton


QA-0115A/B(SET)(QA-111)

 $QA-0215A/B(SET)_{(QA-211)}$

QA-0615A/B(SET)(QA-611)

Heavy Duty Air Die Grinder-Set 15pcs







90° Air Angle Die Grinder





20 pieces are packed in one carton

- 0 1pc Air Die Grinder
- 1pc Collet (3 mm or 1/8")
- 2pcs Spanner Wrench
- 5pcs Grinder Stone (3 mm or 1/8")
- 5pcs Shank Stone (6 mm or 1/4")
- 1pc Plug (adapter)



	Collet Size	Collet Size	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Motor	Net Weight	Air Hose	Sound Pressure	Vibration Level
	A mm	B inch	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	HP	LBS(kg)	Inch	dBA	m/s²
		◯	No	□ □ □ ¢		l+ L	hp	lb kg	□	?)))	(((O)))
QA-111	6 & 3	1/4" & 1/8"	25000	10.0(283)	90(6.3)	6"(155)	0.3	0.84 0.38	3/8"	81.5	1.8
QA-311	6 & 3	1/4" & 1/8"	25000	10.0(283)	90(6.3)	7-1/2"(190)	0.3	1.06 0.48	3/8"	81.5	1.8
QA-313	6 & 3	1/4" & 1/8"	25000	10.0(283)	90(6.3)	9-1/4"(235)	0.3	1.28 0.58	3/8"	81.5	1.8
QA-315	6 & 3	1/4" & 1/8"	25000	10.0(283)	90(6.3)	11"(280)	0.3	1.39 0.63	3/8"	81.5	1.8
QA-211	6 & 3	1/4" & 1/8"	20000	10.0(283)	90(6.3)	7-1/2"(190)	0.9	1.43 0.65	3/8"	75.7	0.8
QA-611	6 & 3	1/4" & 1/8"	19000	10.0(283)	90(6.3)	6-1/8"(160)	0.3	1.12 0.51	3/8"	74.4	1.7

MIGRO AIR Compair to solution of the Compair to Complete air tool



A: 3mm B: 1/8"

Micro Air Die Grinder



A: 3mm B: 1/8" Micro Air Die Grinder



















20 pieces are packed in one carton



QA-432 A: 3mm B: 1/8"

Micro Air Die Grinder



QA-511

Engraving Pen









20 pieces are packed in one carton












20 pieces are packed in one carton

	Collet Size inch(mm)	Free Speed R.P.M	Blow Per Minute	Avg. Air Consumption CFM (L/min)	Air Pressure PSI (bar)	Overall Length	Hose Length	Net Weight LBS(kg)	Air Hose	Sound Pressure	Vibration Level m/s²
		No	bpm	₽₩		I 	_	lb kg	<u>↓</u>	?)))	(((O)))
QA-412	1/8" (3)	60000		2.7(76)	90(6.3)	6-3/4"(170)	1500	0.53 0.24	3/8"	70.0	0.5
QA-421	1/8" (3)	60000		2.7(76)	90(6.3)	6"(150)	1500	0.49 0.22	3/8"	70.0	0.5
QA-432	1/8" (3)	70000		1.0(29)	90(6.3)	5-3/8"(137)	1425	0.4 0.20	3/8"	70.0	0.5
QA-511			13000	1.0(29)	90(6.3)	5-1/2"(140)	1420	0.5 0.23	3/8"	78.0	0.6







QB-104 / QB-105

Air Angle Grinder / Roll Type Throttle

Note: The grinding wheel is not supplied along with the tool









10 pieces are packed in one carton



QB-114 / QB-115

Air Angle Grinder / Lever Type Throttle

Note: The grinding wheel is not supplied along with the tool









10 pieces are packed in one carton



QB-124 / QB-125

Air Angle Grinder / Lever Type Throttle

Note: The grinding wheel is not supplied along with the tool









8 pieces are packed in one carton



QB-134 / QB-135

Air Angle Grinder / Lever Type Throttle

Note: The grinding wheel is not supplied along with the tool







10 pieces are packed in one carton

AIR ANGLE GRINDER

SUPPORT | VALUE | EXPERTISE



QB-144 / QB-145

Air Angle Grinder / Roll Type Throttle

Note: The grinding wheel is not supplied along with the tool



QB-154 / QB-155

Air Angle Grinder / Lever Type Throttle

Note: The grinding wheel is not supplied along with the tool







10 pieces are packed in one carton







10 pieces are packed in one carton



QB-164 / QB-165

Air Angle Grinder / Roll Type Throttle

Note: The grinding wheel is not supplied along with the tool







10 pieces are packed in one carton

	Pad Dia	Spindle Size	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Motor	Ne Weig	ght	Air Hose	Sound Pressure	Vibration Level
			N ₀	□ Þ 			hp	(lb)	kg	□	?)))	(((O)))
QB-104	4"(100)	3/8"-24	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-105	5"(125)	3/8"-24	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.1	1.2
QB-114	4"(100)	3/8"-24	11000	6.0(170)	90(6.3)	9"(230)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-115	5"(125)	3/8"-24	11000	6.0(170)	90(6.3)	9"(230)	0.78	4.0	1.81	3/8"	87.1	1.2
QB-124	4"(100)	3/8"-24	11000	6.0(170)	90(6.3)	9"(230)	0.80	3.8	1.73	3/8"	85.7	3.0
QB-125	5"(125)	5/8"-11	11000	6.0(170)	90(6.3)	9"(230)	0.80	3.9	1.78	3/8"	87.0	5.9
QB-134	4"(100)	M10xP1.5	11000	6.0(170)	90(6.3)	9"(230)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-135	5"(125)	M14xP2.0	11000	6.0(170)	90(6.3)	9"(230)	0.78	4.0	1.81	3/8"	87.1	1.2
QB-144	4"(100)	M10xP1.5	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-145	5"(125)	M14xP2.0	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-154	4"(100)	3/8"-24	11000	6.0(170)	90(6.3)	9"(230)	0.78	3.8	1.73	3/8"	87.8	1.2
QB-155	5"(125)	3/8"-24	11000	6.0(170)	90(6.3)	9"(230)	0.78	3.8	1.73	3/8"	87.8	1.2
QB-164	4"(100)	3/8"-24	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.8	1.2
QB-165	5"(125)	3/8"-24	11000	6.0(170)	90(6.3)	8-7/8"(226)	0.78	4.0	1.81	3/8"	87.8	1.2



QB-107

Air Angle Grinder / Roll Type Throttle

Note: The grinding wheel is not supplied along with the tool



6 pieces are packed in one carton



QB-117

Air Angle Grinder / Lever Type Throttle

Note: The grinding wheel is not supplied along with the tool



6 pieces are packed in one carton



QB-177

Air Angle Grinder / Lever Type Throttle

Note : The grinding wheel is not supplied along with the tool



QB-179

Air Angle Grinder / Lever Type Throttle

Note : The grinding wheel is not supplied along with the tool





6 pieces are packed in one carton





4 pieces are packed in one carton

	Pad Dia	Spindle Size		Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure PSI (bar)	Overall Length	Motor HP	Net Weight LBS(kg)	Air Hose Inch	Sound Pressure	Vibration Level
				№	□ ⊧			hp	(Ib)	(g)	%)))	(((O)))
QB- 107	7"(178)		1	7000	9.0(255)	90(6.3)	11-1/4"(290)	1.0	7.1 3.	24 1/2"	89.7	1.0
QB- 117			1	7000	9.0(255)	90(6.3)	13-1/2"(343)	1.0	7.1 3.	24 1/2"	89.7	1.0
QB- 177		5/8"-11		7600	6.0(170)	90(6.3)	11-13/16"(170)	1.0	7.26 3.		92.0	2.7
QB- 179	9"(230)	5/8"-11		6000	7.0(198)	90(6.3)	11"(279)	3.8	13.2 6.	.0 3/4"	86.0	2.1







QB-311 Air Belt Sander











20 pieces are packed in one carton



QB-312 Air Belt Sander















QB-313

Air Belt Sander











6 pieces are packed in one carton

QB-91108 QB-91110 QB-91208 QB-91210



Item No.	Belt Size
QB-91108	10m x 330mm #80
QB-91110	10m x 330mm #100
QB-91208	20m x 520mm #80
QB-91210	20m x 520mm #100

AIR BELT SANDER

SUPPORT | VALUE | EXPERTISE




10 pieces are packed in one carton

10 pieces are packed in one carton



	Belt Size Pad Dia inch(mm)	Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure	Overall Length	Motor HP		Net /eight	Air Hose	Sound Pressure	Vibration Level
		№	□ •		I + 	hp	lb)	kg	□ <u></u>	<i>((()</i>	(((O)))
QB-311	3/8"x13"(10x330)	16000	8.0(226)	90(6.3)	11-1/2"(290)		1.76	0.80	3/8"	89.7	0.5
QB-312	3/4"x19"(20x520)	16000	9.0(254)	90(6.3)	14"(360)	·	2.65	1.20	3/8"	91.8	0.4
QB-313	1-3/16"x21-1/4"(30x540)	13000	10.0(283)	90(6.3)	15-3/8"(390)		5.28	2.4	3/8"	81.0	1.2
QB-321	3/8"x13"(10x330)	16000	4.0(113)	90(6.3)	12-5/8"(320)		2.10	0.95	3/8"	88.0	1.0
QB-322	3/4"x19"(20x520)	16000	4.0(113)	90(6.3)	17"(430)		3.10	1.40	3/8"	88.0	1.3
		16000	4.0(113)	90(6.3)	18"(455)		2.4	1.10	3/8"	88.0	1.1
QB-324	1/2"x24"(12.7x610)	10000	7.0(113)							-1	



AIR SANDER

SUPPORT | VALUE | EXPERTISE



QB-52
Air Random Orbital Sander
Non-Vacuum









8 pieces are packed in one carton



QB-53

Air Random Orbital Sander Self-Generated Vacuum









8 pieces are packed in one carton





QB-48111

Air Random Orbital Sander Non-Vacuum

Spring cock can reduce the material cost of abrasive paper.

O Elastic mechanism for durability and long lifespan.

 Lower body with low center designed, while operating can be steady with face.

12 pieces are packed in one carton



	Pad Dia	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Motor	Net Weight		Air Hose	Sound Pressure	Vibration Level	orbit
	inch(mm)	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	HP	LBS	(kg)	Inch	dBA	m/s²	mm
		№	□ • 		l - L →l	hp	(lb)	kg	<u></u>	(((§	(((O)))	\bigcirc
QB-52502	5"(127)	10000	6(170)	90(6.3)	6"(153)	0.24	2.2	1.00	3/8"	87.6	0.7	5
QB-52602	6"(152)	10000	6(170)	90(6.3)	6-1/2"(166)	0.24	2.65	1.20	3/8"	87.6	1.7	5
QB-53802	5"(127)	10000	6(170)	90(6.3)	6"(153)	0.24	2.2	1.00	3/8"	86.2	0.5	5
QB-53902	6"(152)	10000	6(170)	90(6.3)	6-1/2"(166)	0.24	2.65	1.20	3/8"	80.1	1.2	5
	4"x4-3/8"(100x110)	11000	7.0(198)	90(6.3)	5-1/5"(130)	0.28	2.0	0.91	3/8"	83.0	1.5	2.5







AIR SANDER

SUPPORT | VALUE | EXPERTISE



QB-41

Air Random Orbital Sander Central-Vacuum











10 pieces are packed in one carton



QB-42

Air Random Orbital Sander Non-Vacuum











10 pieces are packed in one carton



QB-43

Air Random Orbital Sander











6 pieces are packed in one carton

	Pad Dia	Free Speed	•		Overall Length	Motor	Net Weight		Air Hose	Sound Pressure	Vibration Level	orbit
	inch(mm)	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	HP	LBS(kg)		Inch	dBA	m/s²	mm
		№	□ ⊧≑			hp	(Ib)	(kg)	<u>↓</u>	(((§	((O)))	0
QB-45602	6"(152)	10000	3.85(109)	90(6.3)	7-1/2"(193)	0.24	1.85	0.84	3/8"	81.6	7.1	5
QB-46502	5"(127)	10000	3.85(109)	90(6.3)	6"(153)	0.24	1.74	0.79	3/8"	80.1	7.1	5
QB-46602	6"(152)	10000	3.85(109)	90(6.3)	6-1/2"(166)	0.24	1.74	0.79	3/8"	80.1	7.1	5
QB-47602	6"(152)	10000	3.85(109)	90(6.3)	7-1/2"(193)	0.24	2.49	1.13	3/8"	84.7	7.1	5
QB-41902	6"(152)	10000	3.85(109)	90(6.3)	8"(206)	0.24	2.0	0.91	3/8"	81.5	0.8	5
QB-42502	5"(127)	10000	3.85(109)	90(6.3)	6"(153)	0.24	1.78	0.81	3/8"	75.7	0.6	5
QB-42602	6"(152)	10000	3.85(109)	90(6.3)	6-1/2"(166)	0.24	1.87	0.85	3/8"	74.4	1.3	5
B-43802	5"(127)	10000	3.85(109)	90(6.3)	8"(206)	0.24	3.28	1.49	3/8"	83.9	1.3	5
B-43902	6"(152)	10000	3.85(109)	90(6.3)	8-3/4"(221)	0.24	3.39	1.54	3/8"	83.0	1.4	. 5





10 pieces are packed in one carton



10 pieces are packed in one carton



AIR SANDER

SUPPORT | VALUE | EXPERTISE









10 pieces are packed in one carton









10 pieces are packed in one carton

PAD

Air Random Orbital Sander - Accessories



(5"&6")



QB-9326 / SIX HOLE QB-9327 / FIFTEEN HOLE

40 pieces are packed in one carton




QB-9403 Rough(3") •

PAD & SPONGE

Air Pistol Sander - Accessories

QB-9413



QB-9323(3"PAD) .

	Pad Dia	Free Speed R.P.M	Avg. Air Consumption	Air Pressure	Overall Length Inch (mm)	Motor	We	let eight 6(kg)	Air Hose	Sound Pressure	Vibration Level	orbit
		N₀ N₀	□ Þ ‡			hp	(lb)	(kg)	□	?)))	(((O)))	0
QB-54602	6"(152)	10000	3.0(85)	90(6.3)	8-1/4"(210)	0.24	1.70	0.78	3/8"	81.6	7.1	5
QB-55502	5"(127)	10000	3.0(85)	90(6.3)	6-5/32"(157)	0.24	1.43	0.65	3/8"	81.6	7.1	5
QB-55602	6"(152)	10000	3.0(85)	90(6.3)	6-11/16"(157)	0.24	1.50	0.68	3/8"	81.6	7.1	5
QB-56602	6"(152)	10000	3.0(85)	90(6.3)	8-1/4"(210)	0.24	1.70	0.78	3/8"	81.6	7.1	5
QP-113	3"(76)	15000	3.5(99)	90(6.3)	5"(127)	0.40	1.58	0.72	3/8"	74.0	0.3	2.5
			3.5(99)	90(6.3)	5-5/16"(135)	0.40	1.69	0.77	3/8"	74.0	0.3	





QG-102 Air Shear / Straight Type



QG-202 Air Shear / Pistol Type









10 pieces are packed in one carton

10 pieces are packed in one carton









Air Nibbler

- The strengthened punch allows longer lifetime.
- O Rear exhaust reduces the noise level.



	Strokes Per min	Avg. Air Consumption	Air Pressure	Overall Length	Net Weight	Air Hose	Sound Pressure	Vibration Level	
	S.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	LBS kg	Inch	dBA	m/s²	mm
	S.P.M	□ p {		l ← L	lb\ kg\	□	(2))	(((O)))	
		, ;	bar	1		<u> †</u>	: 0 /	1 1	
QG- ₁₀₂	2600	6.0(170)	90(6.3)	10"(254)	2.2 1.0	3/8"	85.8	2.4	1.6
QG- ₂₀₂	2600	6.5(184)	90(6.3)	8-1/4"(210)	2.43 1.1	3/8"	89.1	2.9	1.6
QG-103	2600	3.0 (85)	90(6.3)	7-3/5"(193)	2.2 1.0	3/8"	88.0	2.8	1.6

AIR SHEAR


SUPPORT | VALUE | EXPERTISE





QD-291N







AIR DRILL

SUPPORT | VALUE | EXPERTISE





10 pieces are packed in one carton



10 pieces are packed in one carton





10 pieces are packed in one carton





10 pieces are packed in one carton

	Chuck Size	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Ne Wei		Air Hose	Sound Pressure	Vibration Level
	inch(mm)	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	LBS	kg	Inch	dBA	m/s ²
	!!!!</th <th>₩</th> <th>-</th> <th></th> <th> </th> <th>(Ib)</th> <th>kg</th> <th>□</th> <th>(() ()</th> <th>(((O)))</th>	₩	-		 	(Ib)	kg	□	(() ()	(((O)))
	:		: :		:	;	:	1	1 -	:
QE- 331	3/8"(10)	1800	6.5(184)	90(6.3)	8"(203)	2.42	1.1	3/8"	96.5	0.3
QE- 331 QE- 332	3/8"(10)	2200	6.5(184)	90(6.3)	7-1/2"(190)	2.20	1.0	3/8"	96.5	0.3
		2200		90(6.3) 90(6.3)	7-1/2"(190)	2.20	1.0 1.1	3/8"		0.3





10 pieces are packed in one carton





10 pieces are packed in one carton



10 pieces are packed in one carton



10 pieces are packed in one carton

AIR DRILL

SUPPORT | VALUE | EXPERTISE



10 pieces are packed in one carton



10 pieces are packed in one carton



10 pieces are packed in one carton



10 pieces are packed in one carton

	Chuck Size inch(mm)	Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure PSI (bar)	Overall Length		let ight kg	Air Hose Inch	Sound Pressure	Vibration Level m/s ²
	√	N _o	□ ⊧			(Ib)	kg	□	?)))	(((O)))
QE-341	1/2"(13)	800	6.5(184)	90(6.3)	9"(230)	3.96	1.8	3/8"	96.5	0.1
QE-342	1/2"(13)	800	6.5(184)	90(6.3)	8-1/4"(209)	3.74	1.7	3/8"	96.5	0.1
QE-343	1/2"(13)	800	6.5(184)	90(6.3)	9"(230)	3.96	1.8	3/8"	97.5	0.1
QE-344	1/2"(13)	800	6.5(184)	90(6.3)	8-1/4"(209)	3.74	1.7	3/8"	97.5	0.1
QE-431	3/8"(10)	1800	4.0(112)	90(6.3)	8-29/32"(226)	2.6	1.18	3/8"	90.0	3.0
QE-432	3/8"(10)	2200	4.8(135)	90(6.3)	8-29/32"(226)	2.6	1.18	3/8"	90.0	3.0
QE-433	3/8"(10)	1800	4.0(112)	90(6.3)	9-1/16"(230)	2.7	1.65	3/8"	90.0	3.0
QE-434	3/8"(10)	2200	4.8(135)	90(6.3)	9-1/16"(230)	2.7	1.65	3/8"	90.0	3.0







10 pieces are packed in one carton

10 pieces are packed in one carton

AIR DRILL

SUPPORT | VALUE | EXPERTISE



QE-532

3/8"Air Drill With Keyless Chuck













10 pieces are packed in one carton



QE-533

3/8"Air Reversible Drill With Key Chuck











10 pieces are packed in one carton



QE-542

1/2"Air Drill With Keyless Chuck



















10 pieces are packed in one carton





1/2"Air Reversible Drill With Key Chuck













10 pieces are packed in one carton

	Chuck Size inch(mm)	Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure PSI (bar)	Overall Length	Wei	et ight S(kg)	Air Hose	Sound Pressure	Vibration Level m/s ²
	< <u>†</u>	№	□ Þ ≑			(lb)	kg	<u></u>	(((§))	((O))
QE-441	1/2"(13)	1100	4.0(112)	90(6.3)	10-53/64"(270)	3.5	1.58	3/8"	90.0	3.0
QE-442	1/2"(13)	1300	4.8(135)	90(6.3)	10-53/64"(270)	3.5	1.58	3/8"	90.0	3.0
QE-443	1/2"(13)	1100	4.0(112)	90(6.3)	10-53/64"(270)	3.8	1.73	3/8"	90.0	3.0
QE-444	1/2"(13)	1300	4.8(135)	90(6.3)	10-53/64"(270)	3.8	1.73	3/8"	90.0	3.0
QE-532	3/8"(10)	2800	4.8(135)	90(6.3)	9-9/16"(243)	2.7	1.25	3/8"	90.0	2.0
QE-533	3/8"(10)	2200	4.0(112)	90(6.3)	9-13/32"(189)	2.7	1.25	3/8"	90.0	2.0
QE-542	1/2"(13)	1300	4.8(135)	90(6.3)	11-1/64"(280)	3.8	1.75	3/8"	90.0	2.0
QE-543	1/2"(13)	1100	4.0(112)	90(6.3)	10-55/64"(276)	3.8	1.75	3/8"	90.0	2.0











QE-831 3/8"(10) 1800 4.0(113) 90(6.3) 7-1/4"(185) 2.5 1.10 3/8" 83.0 0.3 QE-833 3/8"(10) 1800 4.0(113) 90(6.3) 7-1/4"(185) 2.5 1.10 3/8" 83.0 0.3		Chuck Size	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length	Net Weight	Air Hose	Sound Pressure	Vibration Level
QE- 833 3/8"(10) 1800 4.0(113) 90(6.3) 7-1/4"(185) 2.5 1.10 3/8" 83.0 0.3		inch(mm)	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	<u> </u>	: 1	(BA	:
QE- 833 3/8"(10) 1800 4.0(113) 90(6.3) 7-1/4"(185) 2.5 1.10 3/8" 83.0 0.3	QE- 831				90(6.3)					0.3
QE-841 1/2"(13) 800 4.0(113) 90(6.3) 8-1/4"(185) 3.7 1.70 3/8" 83.0 0.3								3/8"	83.0	















20 pieces are packed in one carton

AIR SCREWDRIVER

SUPPORT | VALUE | EXPERTISE



20 pieces are packed in one carton



10 pieces are packed in one carton



12 pieces are packed in one carton



	Chuck Size	Torque Range FT-LB(Nm)	Free Speed R.P.M	Avg. Air Consumption CFM (L/min)	Air Pressure	Overall Length		let eight kg	Air Hose Inch	Sound Pressure	Vibration Level
	¥		№	□ □•;	2 P P P P P P P P P P P P P P P P P P P	l ∗ L →l	(lb)	kg	□	?)))	(((O)))
RA- 101	1/4"(6.35)	3.7-8.9(5-12)	9000	6.0(170)	90(6.3)	6-1/2"(166)	1.32	0.6	3/8"	85.7	2.2
RA- 102	1/4"(6.35)	3.7-10.3(5-14)	9000	6.0(170)	90(6.3)	6-3/4"(172)	1.54	0.7	3/8"	86.7	3.7
RA- 105	1/4"(6.35)	3.7-16.2(5-22)	8500	8.5(241)	90(6.3)	8-1/4"(208)	2.2	1.0	3/8"	96.7	4.9
RA- 110	1/4"(6.35)	70(95)	8500	8.5(241)	90(6.3)	8-1/4"(208)	2.2	1.0	3/8"	96.7	4.9
RA- 111	3/8"(10.0)	120(163)	8500	8.5(255)	90(6.3)	8-1/4"(208)	2.2	1.0	3/8"	96.7	4.9
RA- 201	1/4"(6.35)	3.7-18.5(5-25)	10000	9.0(255)	90(6.3)	7"(180)	2.65	1.2	3/8"	93.0	5.3
RA- 606	1/4"(6.35)	60(81)	8000	5.6(160)	90(6.3)	7-4/5"(198)	2.2	1.0	3/8"	82.0	2.2
RA- 608	1/4"(6.35)	100(135)	8000	4.6(130)	90(6.3)	8-9/16"(217)	2.86	1.3	3/8"	86.0	3.5





RA-301

Air Screwdriver Adjustable Clutch







10 pieces are packed in one carton



RA-302

Air Screwdriver Adjustable Clutch







10 pieces are packed in one carton



RA-801

Air Screwdriver **Adjustable Clutch**









10 pieces are packed in one carton



RA-802

Air Screwdriver **Adjustable Clutch**









10 pieces are packed in one of

	Chuck Size	Torque Range FT-LB(Nm)	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length		et ight kg	Air Hose	Sound Pressure	Vibration Level
	 		No		(i)	l ≪ L ►I	(lb)	kg	: 1	?)))	(((O)))
RA-301	1/4"(6.35)	3.8-10(5-13.5)	1800	6.0(170)	90(6.3)	7-1/2"(190)	2.43	1.1	3/8"	95.3	4.2
RA-302	1/4"(6.35)	3.8-12(5-16.3)	800	6.0(170)	90(6.3)	9"(226)	2.87	1.3	3/8"	96.5	2.2
RA-801	1/4"(6.35)	3.8-10.4(5-14)	1800	4.0(113)	90(6.3)	7-3/4"(195)	2.70	1.2	3/8"	83.0	4.2
RA-802	1/4"(6.35)	3 8-13 3(5-18)	800	4.0(113)	90(6.3)	8-9/32"(210)	2.87	13	3/8"	83.0	4.2

AIR SCREWDRIVER

SUPPORT | VALUE | EXPERTISE





RA-3011 / RA-3017 / RA-3023 RA-4008 / RA-4015 / RA-4021 RA-5005 / RA-5008 / RA-5017

Shut-off Screwdriver

- Proved by the life-time tester, these items can be operated continuously up to 1.5 million times.
- Industrial grade, excellent for long continous operation on various mass production lines.
- Precise machined components, unique internal mechanism design.
- Low noise and vibration rate, high adjustable accuracy up to + - 5%.
- Pressing to start level, ergonomic design, compact volume, light weight, easy and comfortable to operate.





	Chuck Size	Torque Range	Free Speed	Avg. Air Consumption	Air Pressure	Overall Length		et ight	Air Hose	Sound Pressure	Vibration Level
	inch(mm)	IN-LB(Nm)	R.P.M	CFM (L/min)	PSI (bar)	Inch (mm)	LBS	kg	Inch	dBA	m/s²
	Ħ		№	■Þŧ		l ← L →l	(lb)	(kg)	□	?)))	(((O)))
RA-3011	1/4"(6.35)	9.7-18.5(1.1-2.1)	1100	7.0(198)	90(6.3)	7-3/8"(187)	0.94	0.42	1/4"	70.0	2.0
RA-3017	1/4"(6.35)	6.2-13.2(0.7-1.5)	1700	7.0(198)	90(6.3)	7-3/8"(187)	0.94	0.42	1/4"	70.0	2.0
RA-3023	1/4"(6.35)	3.5-8.8(0.4-1.0)	2300	7.0(198)	90(6.3)	7-3/8"(187)	0.94	0.42	1/4"	70.0	2.0
RA-4008	1/4"(6.35)	14.1-35.4(1.6-4.0)	800	10.5(297)	90(6.3)	8-1/4"(209)	1.43	0.65	1/4"	74.0	2.5
RA-4015	1/4"(6.35)	8.8-19.4(1.0-2.2)	1500	10.5(297)	90(6.3)	8-1/4"(209)	1.43	0.65	1/4"	74.0	2.5
RA-4021	1/4"(6.35)	8.8-13.2(1.0-1.7)	2100	10.5(297)	90(6.3)	8-1/4"(209)	1.43	0.65	1/4"	74.0	2.5
RA-5005	1/4"(6.35)	44.2-92.9(5.0-10.5)	480	17.5(495)	90(6.3)	9-1/2"(240)	2.2	1.0	3/8"	75.0	10
RA-5008	1/4"(6.35)	26.5-48.6(3.0-5.5)	800	17.5(495)	90(6.3)	9-1/2"(240)	2.2	1.0	3/8"	75.0	10
RA-5017	1/4"(6.35)	13.2-23.0(1.5-2.6)	1700	17.5(495)	90(6.3)	9-1/2"(240)	2.2	1.0	3/8"	75.0	10

SPRING Complete air tool solutions SALANGER PLUS

SP-101 / SP-102 / SP-103 SP-104 / SP-105 / SP-111 SP-112 / SP-113

Spring Balancer

<u>m7</u>

20 pieces are packed in one carton



SP-212 / SP-213

Spring Balancer

	Capacity	Travel	Rope	Rope Dia	Weight
	Kg (LBS)	m		mm(inch)	kg(LBS)
	kg	l ∗ L →l		Ø	kg
SP- 101	0.3~0.8(0.66-1.76)	1.6	Cable	2.5(0.1")	0.49(1.08)
SP- 102	0.6~1.5(1.32-3.30)	1.6	Cable	2.5(0.1")	0.52(1.14)
SP- 103	1.0~2.0(2.20-4.40)	1.6	Cable	2.5(0.1")	0.53(1.16)
SP- 104	1.5~3.0(3.30-6.60)	1.5	Cable	3.2(0.13")	0.76(1.67)
SP- 105	3.0~5.0(6.60-11.0)	1.5	Cable	3.2(0.13")	0.81(1.78)
SP- 111	0.3~0.8(0.66-1.76)	1.6	Nylon	2.5(0.1")	0.49(1.08)
SP- 112	0.6~1.5(1.32-3.30)	1.6	Nylon	2.5(0.1")	0.52(1.14)
SP- 113	1.0~2.0(2.20-4.40)	1.6	Nylon	2.5(0.1")	0.53(1.16)
SP- 212	0.3~1.2(0.66-2.64)	1.6	Nylon	4.0(0.16")	0.57(1.25)
SP- 213	0.8~2.0(1.76-4.40)	1.6	Nylon	4.0(0.16")	0.57(1.25)















Air Hammer Round Shank Air Hammer Hex Shank

SC-4 chisel kit is provided along with the tool. 8 pieces are packed in one carton











SC-212C





SC-4 chisel kit is provided along with the tool.

8 pieces are packed in one carton









SC-2A Retainer



- O Flat Chisel
- Cutting Chisel
- O Tapered Punch
- Ripping Chisel
- Tail Pipe Cutter



- SC-415 Chisel Set / 175mmL / Round
 SC-425 Chisel Set / 175mmL / Hex

SC-07C

Air Hammer-Set 7pcs

- 1pc- Air Hammer (Various Selections)
- o 5pcs-Chisel Kits
- 1pc- Spring Retainer

Item No.	Shank	Contents
SC-0517C	Round Shank	Round Shank
SC-0527C	Round Shank	Round Shank
SC-0617C	Hex Shank	Hex Shank
SC-0627C	Hex Shank	Hex Shank



AIR HAMMER

SUPPORT | VALUE | EXPERTISE





10 pieces are packed in one carton










	Shank	Chuck Size	Stroke Length	Bolw Per Minute	Avg. Air Consumption	Air Pressure	Overall Length	Net Weig		Air Hose	Sound Pressure	Vibration Level
		inch(mm)	mm	bpm	CFM (L/min)	PSI (bar)	Inch (mm)	LBS	kg	Inch	dBA	m/s²
	•••	<u></u>	_	bpm	₽₹			(Ib)	kg	□	?)))	(((O)))
SC- 211C	•	0.401(10.2)		3200	4.0(113)	90(6.3)	6-7/8"(175)	3.74	1.7	3/8"	98.0	12.3
SC- 221C		0.393(10)		3200	4.0(113)	90(6.3)	6-7/8"(175)	3.74	1.7	3/8"	98.0	12.3
SC- 212C	•	0.401(10.2)		2200	4.0(113)	90(6.3)	8-7/8"(225)	4.40	2.0	3/8"	94.7	13.2
SC- 222C	•	0.393(10)		2200	4.0(113)	90(6.3)	8-7/8"(225)	4.40	2.0	3/8"	94.7	13.2
SN- 1032		0.51(13)		4000	4.23(120)	90(6.3)	11-1/2"(290)	2.92	1.33	3/8"	91.0	14.5
SN- 1268			28	4600	15(424)	90(6.3)	18-1/8"(460)	6.16	2.8	3/8"	91.0	13.7
SN- 1288			32	5500	3(84.96)	90(6.3)	11-3/8"(290)	2.86	1.3	3/8"	86.0	7.67
SN- 2110			33	3700	15(84.96)	90(6.3)	13"(330)	6.16	2.8	3/8"	97.0	9.7



AIR HYDRAULIC RIVETER

SUPPORT | VALUE | EXPERTISE

	MATERIAL			RIVET	DIAMETI	ER(ØMI	M)			
DIVET	RIVET	MANDREL	(2.5)		,	4.0		,	6.4	7.2	8.0
RIVET			2.4	3	.2		4	.8			
	aluminum	aluminum			! ! !						
PA-111	aluminum	steel				_		i 			
PATITI	steel	steel									
	stainless stainless	steel stainless									
	Stairiless	Stairliess			! ! !			1			
	aluminum	aluminum							-		
PA-201	aluminum	steel							=		
	steel stainless	steel steel									
	stainless	stainless									
	aluminum	aluminum									\dashv
DA 201V	aluminum	steel									
PA-201V	steel	steel							-		
	stainless	steel									
	stainless	stainless							-		
	aluminum	aluminum							-		
PA-211	aluminum steel	steel									
	stainless	steel steel									
	stainless	stainless									
	aluminum	aluminum							+		\dashv
	aluminum	steel									
PA-301	steel	steel	_								
	stainless	steel				•					
	stainless	stainless									
	aluminum	aluminum									
PA-301V	aluminum	steel									
IAGGIL	steel	steel									
	stainless stainless	steel stainless									
						-			+		\dashv
	aluminum aluminum	aluminum steel									
PA-301MV	steel	steel									
	stainless	steel				į					
	stainless	stainless				•					
	aluminum	aluminum									
DE 001	aluminum	steel									
PA-321	steel	steel									
	stainless stainless	steel stainless									
									+		
	aluminum	aluminum			! ! !			1	•		
PA-202	aluminum steel	steel steel									
I A LUL	stainless	steel									
	stainless	stainless									
	aluminum	aluminum							+		\dashv
	aluminum	steel									
PA-312	steel	steel									
	stainless	steel				i					
	stainless	stainless			1	•		! !			
	aluminum	aluminum				;		!	1		\dashv
DR 40111	aluminum	steel									
PA-401V	steel	steel						! ! !			
	stainless	steel									
	stainless	stainless									
	aluminum	aluminum									\neg
DR 4011	aluminum	steel						: ! !			
PA-401MV	steel	steel						! ! !			
	stainless	steel	_								
	stainless	stainless				1			1		i





PA-111
Air Hydraulic Riveter









6 pieces are packed in one carton



PA-201
Air Hydraulic Riveter









6 pieces are packed in one carton



PA-211
Air Hydraulic Riveter









6 pieces are packed in one carton



PA-301
Air Hydraulic Riveter









10 pieces are packed in one carton

AIR HYDRAULIC RIVETER

SUPPORT | VALUE | EXPERTISE





6 pieces are packed in one carton





6 pieces are packed in one carton



PA-541
Air Huck Riveter



6 pieces are packed in one carton



PB-2402
Air Hydaulic Nut Setter







6 pieces are packed in one carton

	Traction Power	Stroke Length	Capacity	Air Pressure	Avg. Air Consumption	1.00	Net Weight	Air Hose	Sound Pressure	Vibration Level
	lbf(kgf)	mm	mm	PSI (bar)	L/cycle	LBS		Inch	dBA .	m/s²
	>	l →	+	(Z) (B) (D) (D) (D) (D) (D) (D) (D) (D) (D) (D	₽÷	(lb	kg	□	<i>((()</i>	(((O)))
PA- 111	4100(1860)	26	4.8-8.0	90(6.3)	2.88	6.6	3.0	3/8"	82.0	0.8
PA- 201	3534(1603)	14	2.4-6.4	90(6.3)	2.32	3.9	1.8	3/8"	79.7	0.5
PA- 211	3748(1700)	18	2.4-6.4	90(6.3)	2.9	3.85		3/8"	79.7	0.8
PA- 321	2612(1185)	22	2.4-4.8	90(6.3)	1.48	3.3	1.5	3/8"	79.7	0.4
PA- 301	2303(1045)	16	2.4-4.8	90(6.3)	1.48	3.3	1.5	3/8"	79.7	0.3
PA- 531	4100(1860)	23	4.76	90(6.3)	2.88	6.6	3.0	3/8"	82.0	0.8
PA- 541	4100(1860)	23	6.35	90(6.3)	2.88	6.6	3.0	3/8"	82.0	0.8
PB- 2402	3638(1650)	9	Steel M4~M10 Stainless M4~M8	90(6.3)	1.50	3.41	1.55	3/8"	82.0	0.8





PA-201V
Air Hydraulic Riveter Vaccum Type









6 pieces are packed in one carton



PA-301V
Air Hydraulic Riveter Vaccum Type









6 pieces are packed in one carton



PA-301MV Air Hydraulic Riveter Vaccum Type







6 pieces are packed in one carton



PA-401V
Air Hydraulic Riveter Vaccum Type







6 pieces are packed in one carton

AIR HYDRAULIC RIVETER

SUPPORT | VALUE | EXPERTISE



° PA-401MV

Air Hydraulic Riveter Vaccum Type





6 pieces are packed in one carton



PA-202 Air Hydraulic Riveter





6 pieces are packed in one carton



PA-312

Air Hydraulic Riveter






6 pieces are packed in one carton

PA-MC


Automatic Mandrel Collection CONTENTS

3/32"(2.4mm) 220pcs 1/8" (3.2mm) 160pcs 5/32"(4.0mm) 110pcs 3/16"(4.8mm) 80pcs





						11/						
	Traction Power	Stroke Length	Capacity	Air Pressure	Avg. Air Consumption	We	Net eight BS(kg)	Air Hose	Sound Pressure	Vibration Level		
	>=		+		□ Þ ≑	(lb)	kg	□	<i>§</i>)))	(((O)))		
PA- 201V	3534(1603)	14	2.4-6.4	90(6.3)	2.32	3.93	1.79	3/8"	79.7	0.5		
PA- 301V	2303(1045)	16	2.4-4.8	90(6.3)	1.48	3.3	1.5	3/8"	79.7	0.3		
PA- 301MV	2303(1045)	16	2.4-4.8	90(6.3)	1.48	3.3	1.5	3/8"	79.7	0.3		
PA- 401V	1532(695)	16	2.4-4.0	90(6.3)	0.67	2.57	1.25	3/8"	79.7	0.3		
PA- 401MV	1532(695)	16	2.4-4.0	90(6.3)	0.67	2.57	1.25	3/8"	79.7	0.3		
I A TOTIM										0.3		
PA- 202	2460(1200)	14	3.2-6.4	90(6.3)	1.8	4.2	1.91	3/8"	79.7	0.5		



AIR GREASE GUN

SUPPORT | VALUE | EXPERTISE









SG-401

Air Grease Gun / Continuous Type

• Heavy duty cast aluminum body for maximum durability

O Working pressure: 40-90 psi

Output volume: 288ml/min

10 pieces are packed in one carton

SG-101
Lubrication Kit
50 pieces are packed in one carton







JC-304 / JC-310 / JC-313 / JC-320 / JC-340



Air Blow Gun

- O Steel nozzle provides long life on the tool.
- O Used for cleaning.
- Special Hi-tech material provide durable, quiet and comfortable operation preventing user fatigue.



50 pieces are packed in one carton



lathing (safe tenon)



50 pieces are packed in one carton



50 pieces are packed in one carton



50 pieces are packed in one carton



AIR BLOW GUN

SUPPORT | VALUE | EXPERTISE

°JC-440

Super Air Blow Gun

20 pieces are packed in one carton





°JC-504 / 510

Air Blow Gun

50 pieces are packed in one carton




JC-507

Air Blow Gun






- O Angle Swivel Blow Gun
- Quick and Easy Setting
- ofor Operation



	Nozzle Length	Working Pressure	Max Pressure	Avg. Air Consumption	Avg. Air Consumption		let ight kg	Sound Pressure	Vibration Level
	l L →l	Working	(MAX)	□ = 1/4" Hous			kg	<u></u>	<i>(</i> 3)))
JC- 304	4"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.15	0.07	3/8"	90.0
JC- 310	10"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.22	0.10	3/8"	90.0
JC- 313	13"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.24	0.11	3/8"	90.0
JC- 320	20"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.31	0.14	3/8"	90.0
JC- 340	40"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.50	0.23	3/8"	90.0
JC- 440	40"	75-120(5.3-8.5)	150(10.6)	13.0(368)	15.0(425)	0.92	0.42	3/8"	90.0
JC- 504	4"	90-120(6.2-8.5)	220(15.1)	13.0(368)	15.0(425)	0.35	0.16	3/8"	80.0
JC- 507	6-1/2"~12"	90-120(6.2-8.5)	220(15.1)	13.0(368)	15.0(425)	0.48	0.22	3/8"	75.0
JC- 510	10"	90-120(6.2-8.5)	220(15.1)	13.0(368)	15.0(425)	0.42	0.19	3/8"	80.0



FILTER, REGULATOR, LUBRICATOR

°SB-201 / SB-215 / SB-304

SUPPORT | VALUE | EXPERTISE




	Max Pressure	Air Consumption at 100PSI	Air Inlet	Air Pressure		let eight	Air Hose	Nozzle Length	Nozzle
	PSI (bar)	CFM	linch	PSI (bar)	LBS	kg	Inch	cm	
		1 , 1				: 0			
	MAX				(lb)	(kg)		l <	
				·					
SB- 201	160(11.0)	1.41	1/4"	90(6.3)	0.70	0.32	3/8"	30	Tyre valve clip
SB- 215	160(11.0)	1.41	1/4"	90(6.3)	0.70	0.32	3/8"	150	Tyre valve clip
SB- 304	160(11.0)	1.41	1/4"	90(6.3)	1.41	0.65	3/8"	30	Tyre valve clip



QK-111







- Lower vibration minimizes the user's fatigue and enables longer operating.
- Lower wear rate of the components prolong the durability of the tool.
- Blade can be mounted in 12 different ways according to user's convenience.















QB-802











FILTER, REGULATOR, LUBRICATOR SUPPORT | VALUE | EXPERTISE





SQ-0217(Set)

Air Powered Brake Caliper Wind Back Tool-Set 17pcs

O Air Powered Brake Caliper Wind Back Tool: 1pc

O Disk: 16pcs

5 pieces are packed in one carton



3.INFORMATION ON ADAPTERS

No.	Application
0	GM most 2-1/2" diameter pistons(seville/Eldored 79)
2	Citoën : XM · Xantia(F/R) HONDA
3	AUDI (F) FIAT Alfa romeo (F) FORD ', Fiesta(F) ISUZU(F) HONDA ', Concesto (F) Jaguar ', XJ6 ', XJ40(F/R) BMW ', 318is ', 320i ', 325TD ', 518i & 1x ', 740i ', 850ci ', M5(F) Mercedes Benz ', 190 ', 200 ', 300 ', 420 ', 560 series(F) Mitsubishi ', Colt(F) NISSAN ', Mlera ', Stanza ', Sunny(F) Rover ', Austin ', Metro 200 & 400 series ', Maestra ', Montego(F) TOYOTA ', Camry(F) VOLVO(F) VW ', Passat ', Golf GTI(F)
4	FORD ', Australia ', NZ Telster MAZDA (R) SAAB ', 9000(R) ', Lumina TOYOTA FIAT Alfa Romeo ', 164 2.0(R) HONDA ', Prelude ', CRS 16i GM ', Saturn(R) ', Grand Prix
5	3/8" adapter
6	NISSAN [,] PRIMERA VW [,] Golf IV
7	AUDI , 80 , 90 , V8+100 , Coupe E(R) Rover , 800 ABS SUBARU , L+Z(R) FORD , Sierra ABS , Granada , Scorpio ABS 85 (R) NISSAN , Biuebird 1.8 Turbo , Silvia Turbo , Primera 2.0iLS/GS/GSX(R) PEUGEOT , 405 1 9Gi , Gri , Sri , Gtxi , Mi 16 , 605 2.0 Sri(R)

No.	Application
7	TOYOTA · Celica · Corolla GT · MR2(R) VW · Golf Gti · jeta Synchro · jetta Gti 16v · Passat CL · GL · GT · GT · 16v Corrado 16V scirroca GTX 16V (R) Citroën Alfa Romeo FIAT HONDA Jaguar Renault SAAB Seat Lancia
8	GM most 1-7/8" diameter pistons
9	GM most 2-1/8" diameter pistons
A(Z)	Renault , R21 , Laguna(R)
E	NISSAN , Maximas FORD
F(G)	Opel(R)
M	Ford Motors MINI R68 MAZDA 3
N	SAAB HONDA Alfa Romen AUDI VW Lancia
K	Cilroën
K1	Cilroën



FILTER, REGULATOR, LUBRICATOR

SUPPORT | VALUE | EXPERTISE

SV-2230 / SV-2330

FILTER, REGULATOR, LUBRICATOR

- O Removes all dirt particles larger than five microns.
- 50c.c. Lubricating oil bowl capacity.
- O Can be filled under pressure.

SV-2431

FILTER, REGULATOR, LUBRICATOR




°SW-12-1/4" / SW-13-3/8"

Mini Lubricator

- Install in the air hose to provide automatic lubrication.
- 8c.c. Lubricating oil capacity.





	Air in / outlet	Working Pressure	Proof Pressure	Regulation Pressure Range	Working Temperature	Min.Flow for Oil Drip	Weight	
	inch	kgf/cm²(Mpa)	kgf/cm ² (Mpa)	kgf/cm²(Mpa)	°C	L/min	LBS(kg)	
	<u> </u>	Morking				<u>_</u>		
		Working					(Ib/kg)	
SV- 2230	1/4"	0-9.9(0-0.99)	15(1.5)	0.5-8.5(0.05-0.85)	5~60°	50	1.59(0.70)	
SV- 2330	3/8"	0-9.9(0-0.99)	15(1.5)	0.5-8.5(0.05-0.85)	5~60°	60	1.59(0.70)	1
SV- 2431	1/2"	0-15 (0-1.5)	20(2.0)	1.0-15(0.1-1.5)	-5~60°	80	3.3(1.50)	



SA-215 / SA-315

Air-Hose Reel

- O Mounting bracket can be mounted on the wall or ceiling.
- \circ 24 braids covered PU tube brings the anti-explosion capability up to 350 psi.
- Auto retractable hose is replaceable and convenient to be stored.
- $_{\odot}$ The durable rewinding spring results in smooth operation.

NOTE:

- 1. Type A: Multi-Copular allows Nitto Asia style plug.
- 2. Type B:Multi-Copular all in one, allows for Milton/ Tru-Flate/ Aro and Orion series European style plug.
- 3. Type C: Multi-Copular allows U.S.A style plug.
- 4. Type D: Multi-Copular allows France style plug.
- 2 pieces are packed in one carton




SD-23

Polyurethane Recoil Air-Hose

• Returns automatically to the original position and keeps it out of operator's way during operation.

 Spring guards protects both ends of the hose. Both ends have male 360° swivel fittings.

 \circ Temperature resistance from -20° C \sim +70° C.



SY-M SY-F Air Adapter / Quick Couplings


Air Adapter

Item No.	Thread Type	Thread Size	Туре	Picture
SY-211M SY-211F	Male Female	1/4" PT	Europe	
SY-221M SY-321M	Male	1/4" PT 3/8" PT	lanan	
SY-221F SY-321F	Female	1/4" PT 3/8" PT	Japan	
SY-231M SY-231F	Male Female	1/4" NPT	U.S.A	

Air Coupler

Item No.	Thread Type	Thread Size	Туре	Picture
SY-210M SY-210F	Male Female	1/4" PT	Europe	
SY-220M SY-320M	Male	1/4" PT 3/8" PT	Japan	
SY-220F SY-320F	Female	1/4" PT 3/8" PT	заран	
SY-230M SY-230F	Male Female	1/4" NPT	U.S.A	

	Hose Inside Diameter	Hose outside Diameter	Hose Length m (inch)	Working Pressure	Break Pressure kg/cm²	Male PT Fitting	Female PT Fitting	Weight kg(LBS)
	□	<u></u>	<u></u> .					(lb/kg)
SA- 215	8.0	12.0	15(590)	7.0	20	1/4"		5.3(11.6)
SA- 315	10.0	15.0	15(590)	7.0	20	3/8"		8.0(17.6)
SD-23110		12.0	10(393)		20	1/4"		
SD-23115	8.0	12.0	15(590)	7.0	20	1/4"		
SD-23210	5.0	8.0	10(393)	7.0	20	1/4"		
SD-23215	5.0	8.0	15(590)	7.0	20	1/4"		
SD-23315	10	15.0	15(590)	7.0	20	3/8"		
SD-24415		18.0	15(590)		20	1/2"		













1/2" MA411M

Impact Standard Socket

- 1/2" drive standard Length
- 0 6 points
- O Metric size





MA-	Size	<u> </u>	BOX / CTN
	mm	g (lbs)	
411M08	8	67(0.14)	10 / 200
411M09	9	67(0.14)	10 / 200
411M10	10	70(0.15)	10 / 200
411M11	11	71(0.15)	10 / 200
411M12	12	72(0.16)	10 / 200
411M13	13	72(0.16)	10 / 200
411M14	14	77(0.17)	10 / 200
411M15	15	112(0.24)	10 / 160
411M16	16	112(0.24)	10 / 160
411M17	17	115(0.25)	10 / 160
411M19	19	120(0.26)	10 / 160
411M21	21	125(0.27)	6 / 120
411M22	22	143(0.31)	6 / 120
411M24	24	152(0.33)	6 / 120
411M27	27	176(0.38)	6/120

3/4" MA611M

Impact Standard Socket

- 3/4" drive standard Length
- 0 6 points
- O Metric size





MA-	Size	₫.	BOX / CTN
	mm	g (lbs)	
611M17	8	67(0.14)	10 / 200
611M19	9	67(0.14)	10 / 200
611M21	10	70(0.15)	10 / 200
611M22	11	71(0.15)	10 / 200
611M24	12	72(0.15)	10 / 200
611M26	13	72(0.15)	10 / 200
611M27	14	77(0.17)	10 / 200
611M29	15	112(0.24)	10 / 160
611M30	16	112(0.24)	10 / 160
611M32	17	115(0.25)	10 / 160
611M35	19	120(0.26)	10 / 160
611M36	21	125(0.27)	6 / 120
611M38	22	143(0.31)	6 / 120
611M55	24	152(0.33)	6 / 120

1/2" MA431M

Impact Deep Socket

- \bigcirc 1/2" drive Deep version
- 0 6 points
- O Metric size



MA-	Size	₽	BOX / CTN
	mm	g (lbs)	
431M13	13	163(0.35)	6 / 120
431M17	17	248(0.62)	6/96
431M19	19	244(0.53)	6/96
431M21	21	237(0.52)	6/96
431M22	22	292(0.64)	5 / 60
431M24	24	304(0.66)	5 / 60
431M27	27	351(0.77)	5 / 60

1" MA811M

Impact Standard Socket

- \bigcirc 1" drive Deep version
- 0 6 points

O Metric size





MA-	Size	$\overline{\mathbb{A}}$	BOX / CTN
	mm	g (lbs)	
811M13	27 5	538(1.18)	6 / 24
811M17	30 5	592(1.30)	6 / 24
811M19	32	579(1.49)	6 / 24
811M21	33 7	700(1.54)	6 / 24
811M22	36 7	729(1.60)	6/24

MA42006M

1/2"Air Stubby Metric Size impact Socket SET

:		:	:
Square Drive	Size	$\triangle \triangle$	Length
inch	mm	g (lbs)	mm
1/2"	13	54(0.12)	28
1/2"	17	70(0.15)	28
1/2"	19	80(0.17)	28
1/2"	21	90(0.19)	28
1/2"	22	100(0.22)	28
1/2"	24	110(0.24)	28

MA42006S

1/2"Air Stubby Inch Size impact Socket SET

So	quare Drive	Size	₫	Length
	inch	inch	g (lbs)	mm
	1/2"	1/2"	54(0.12)	28
	1/2"	9/16"	70(0.15)	28
	1/2"	5/8"	80(0.17)	28
	1/2"	11/16"	90(0.19)	28
	1/2"	3/4"	100(0.22)	28
	1/2"	7/8"	110(0.24)	28

























IMPACT SOCKET

SUPPORT | VALUE | EXPERTISE

MA-4030

Deep Impact Socket Set 3 PCS 1/2" DR.

- O Contents: 17mm, 19mm, 21mm
 - By identifying the different color coated, the operator can
- o easily pick up the size needed.
- With the external sheath, the working odject can be well o protected from being rubbed, scratched,impacted...etc.
- With the 85mm extra long socket, to loosen or tighten bolt or nut in deeper hole become easier and convenient.



3/8" MB371S

3/8" Drive Bit Holder





1/2" MB471 1/2" Drive Bit Holder





1/2" ME4711

1/2" Drive Universal Joint





1/2" ME421

1/2" Drive Extension Bar



3/4" ME6711

3/4" Drive Universal Joint





3/4" ME621


3/4" Drive Extension Bar





3/4" ME016/ME916

3/4" Drive Locking Ring/3/4" Drive Locking Pin





3/4" ME68

3/4" Drive Adapter









AD-35

Complete set of Tool Base

Item No.	Adaptor Type	Contents
AD-3501	Europe	SY-211M AD-3521 AD-351
AD-3502	Japan	AD-351 SY-221M
AD-3503	U.S.A	SY-231M AD-3523 AD-351

AFTER MARKET SUPPORT

SUPPORT | VALUE | EXPERTISE

°AD-306

Table Type Display Stand

- O 1 pc Transparent DM shelf
- O 2 pcs support frame
- 1 pc Bottom shelf
- O 3 set (AD-3521/3522/3523)



Overall Size
Width x Depth x Height

(mm) 300 x 140 x 340

(inch) 11.8" x 5.5" x 13.3"



Packaging All M7 Products Come

All M7 Products Come in Eye-Catching Color Packages







Tower Type Display Stand


- O 1 pc Transparent DM shelf
- O 2 pcs support frame
- 1 pc Bottom shelf
- O 3 set (AD-3521/3522/3523)

			Package		
Contains	net weight kg(lbs)	gross weight kg(lbs)	length mm(inch)	width mm(inch)	height mm(inch)
Lamp Case Set	4.35(9.6)	5.35(11.8)	530(20.8")	510(20.1")	101(10.0")
Display Pillar Display Stand Bottom Plate	8.0(17.6) 10.45(23.0)	9.0(19.8) 11.45(25.2)	930(36.6") 810(31.8")	330(13.0") 820(32.3")	180(7.1") 70(2.7")

AD-305-41
Optional Item

°AD-36

Complete set of Tool Base



Item No.	Adaptor Type	Contents
AD-3601	Europe	SY-211M AD-305-41
AD-3602	Japan	AD-305-41 SY-221M AD-3522
AD-3603	U.S.A	SY-231M AD-3523 AD-305-41

AFTER MARKET REPAIR KITS

SUPPORT | VALUE | EXPERTISE

User's Manual of Air Impact Wrench

Working environment:


- Using these tools in any potentially explosive environment is strictly prohibited.
- It is always recommended that these types of tools must be operated when standing on a solid or firm location.
- O Always use these tools in a well ventilated area.
- Slipping, stumbling and falling are the major causes of potential serious injury, therefore, a clean and clutter free surface in the working area before operating the tools is strongly recommended.

Ideal system connection

Air supply and connection requirements:

- The maximum recommended air pressure during operation must not exceed 90 psi (6.3bar). Higher air pressure may create unsafe operating conditions for the tool and the user.
- The compressed air should be cooled and have a water filter installed at the outlet end of the compressor. Even with a water filter installed, some water may still condense in the piping or hose and will enter the tool mechanism causing premature damage to the tool. Therefore, it is recommended to install an air filter-lubricator device somewhere between the tool and the compressor.
- O Always use an air compressor of the proper capacity to operate each tool.
- Clean the hose with a blast of compressed air before connecting the hose to the air tool. This will prevent both moisture and dust inside the hose from entering the tool and causing possible rust or malfunction.

After Market Repair Kits



M7 provides specialized repairing tools for your after market need

